



Parametric Phase-sensitive and Phase-insensitive All-optical Signal Processing on Multiple Nonlinear Platforms - Invited talk.

Peucheret, Christophe; Da Ros, Francesco; Vukovic, Dragana; Ding, Yunhong; Dalgaard, Kjeld; Galili, Michael; Gajda, A.; Xu, J.; Fukuchi, Y.; Hu, Hao

Total number of authors:
16

Publication date:
2014

Document Version
Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):
Peucheret, C., Da Ros, F., Vukovic, D., Ding, Y., Dalgaard, K., Galili, M., Gajda, A., Xu, J., Fukuchi, Y., Hu, H., Lei, L., Ou, H., Zimmermann, L., Oxenløwe, L. K., Tillack, B., & Petermann, K. (2014). *Parametric Phase-sensitive and Phase-insensitive All-optical Signal Processing on Multiple Nonlinear Platforms - Invited talk..* Abstract from 35th Progress In Electromagnetics Research Symposium , Guangzhou (Canton), China.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Parametric Phase-sensitive and Phase-insensitive All-optical Signal Processing on Multiple Nonlinear Platforms

C. Peucheret^{1,*}, F. Da Ros², D. Vukovic², Y. Ding², K. Dalgaard², M. Galili², A. Gajda^{3,4}, J. Xu⁵, Y. Fukuchi⁶, H. Hu², L. Lei⁵, H. Ou², L. Zimmermann⁴, L. K. Oxenløwe², B. Tillack^{3,4}, and K. Petermann³

¹FOTON Laboratory, CNRS UMR 6082, University of Rennes 1, ENSSAT, 22305 Lannion, France

²Department of Photonics Engineering, Technical University of Denmark, 2800 Kgs. Lyngby, Denmark

³Technische Universität Berlin, Fachgebiet Hochfrequenztechnik, 10587 Berlin, Germany

⁴IHP, 15236 Frankfurt (Oder), Germany

⁵Huazhong University of Science and Technology, Wuhan, 430074, Hubei, China

⁶Department of Electrical Engineering, Tokyo University of Science, Tokyo 125-8585, Japan

*Corresponding author: christophe.peucheret@univ-rennes1.fr

Parametric processes in materials presenting a second- or third-order nonlinearity have been widely used to demonstrate a wide range of all-optical signal processing functionalities, including amplification, wavelength conversion, regeneration, sampling, switching, modulation format conversion, optical phase conjugation, etc. The recent evolution of optical fiber communication systems towards advanced modulation formats making use of the phase dimension, as well as polarization- and, more recently, space-multiplexing, has created new requirements, as well as new opportunities, for parametric all-optical signal processing.

In this presentation, we will review our recent results on the demonstration of all-optical parametric signal processing using different nonlinear platforms, including highly nonlinear optical fibers (HNLFs), silicon nanowires, and periodically-poled lithium niobate (PPLN) waveguides. In particular, we will show how phase-sensitive processes can be engineered to demonstrate phase-quadrature separation, which we have recently demonstrated in HNLFs [1] and PPLN waveguides [2]. Silicon nanowires are particularly attractive for signal processing thanks to their compact size, CMOS-compatible fabrication process, degrees of freedom in dispersion engineering, and high nonlinear coefficient. However, the detrimental effect of free-carrier absorption induced by two-photon absorption has so far prevented them from being used for the demonstration of phase-sensitive processing. Thanks to the introduction of p-i-n junctions across silicon waveguides, we have recently been able to demonstrate phase-sensitive extinction ratios as high as 20 dB, allowing the phase regeneration of phase-modulated signals under continuous wave pumping operation [3]. One of the well-known limitations of planar waveguide devices for all-optical signal processing is their inherent polarization-sensitivity. We will show how the introduction of polarization-diversity circuits relying on efficient and wideband polarization splitters and rotators [4] can overcome this limitation. Finally, we will also discuss the introduction of signal processing functionalities that are compatible with the novel dimension of space multiplexing. More specifically, we will show how mode-selective wavelength conversion based on four-wave mixing can be realized in a multimode silicon waveguide [5].

ACKNOWLEDGMENT

This work was partly funded by the Danish Research Council for Technology and Production Sciences (project 09-066562), the German Research Foundation (DFG) in the framework of Sonderforschungsbereich SFB787, and Villum Fonden via the NATEC Centre.

REFERENCES

1. Da Ros, F., K. Dalgaard, L. Lei, J. Xu and C. Peucheret, "QPSK-to-2×BPSK wavelength and modulation format conversion through phase-sensitive four-wave mixing in a highly nonlinear optical fiber," *Opt. Express*, Vol. 21, No. 23, 28743–28750, 2013.
2. Da Ros, F., K. Dalgaard, Y. Fukuchi, J. Xu, M. Galili and C. Peucheret, "Simultaneous QPSK-to-2×BPSK wavelength and modulation format conversion in PPLN," to appear in *IEEE Photon. Technol. Lett.*, 2014.
3. Da Ros, F., D. Vukovic, A. Gajda, K. Dalgaard, L. Zimmermann, B. Tillack, M. Galili, K. Petermann and C. Peucheret, "Phase regeneration of DPSK signals in a silicon waveguide with reverse-biased p-i-n junction," *Opt. Express*, Vol. 22, No. 5, 5029–5036, 2014.
4. Ding, Y., H. Ou and C. Peucheret, "Wideband polarization splitter and rotator with large fabrication tolerance and simple fabrication process," *Opt. Lett.*, Vol. 38, No. 8, 1227–1229, 2013.
5. Ding, Y., J. Xu, H. Ou and C. Peucheret, "Mode-selective wavelength conversion based on four-wave mixing in a multimode silicon waveguide," *Opt. Express*, Vol. 22, No. 1, 127–135, 2014.